

SPECIFICATIONS AR SERIES RANGE HOODS

180 CFM/7.0 Sones @ 0.10" WG. Horizontal, 180 CFM/7.5 Sones @ 0.10"WG. Vertical, 120 Volts, 2.1 amps, 60hz

Dimensions

Overall bottom projection - 183/8" Overall top projection -12" Height - 6". Available widths: 30" & 36"

Hood Body

23 gauge cold rolled steel, auto welded, coated with a baked enamel finish.

Motor

2 speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, 60 hz., 2.1 amps. Complete with 200°C lead wires.

Lighting

Single 75 watt cook light capacity (bulb not included).

Ducting Options


Vertical ducting: 7" round (duct collar built into hood).

Fan Blade


One piece polymeric, electronically balanced blade. 65/8" diameter with 5 paddles.

Electrical connection

Hood top - 7/8" electrical knockout. Hood back - 7/8" electrical knockout.



AR SERIES



Filters

UL rated, class 2 filter. Grease Filter: RF35 - 87/8"x103/8" (included).

Available Finishes

White, Biscuit, Almond, Black & Stainless Steel.

HVI PERFORMANCE										
Static Pressure (inches of w.g.)	0	0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4	
CFM	246	232	218	203	181	147	125	99	70	
RPM	3056	3010	2973	3007	2939	2744	2536	2283	2107	
WATTS	87	87	87	87	86	86	86	86	86	

Air-King range hoods are tested by the Air Movement and Control Association (AMCA) in accordance with HVI test standard 916, (Air Flow Test Standard) and HVI test standard 915 (Procedure For Loudness Rating Of Residential Fan Products). The Performance results are certified and verified by the Home Ventilating Institute (HVI).

PROJECT						ARCHITE	т	
LOCATION						ENGINEE	R	
CONTRACTOR						SUBMITT	ED BY	DATE
FAN MODEL NUMBER NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	ΩТΥ	OPTIONAL EQUIPMENT & REMARKS





U.S.: 820 Lincoln Drive West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785

Tel: (610) 692-7400 • 877-304-3

Canada: 110 Glidden Road Brampton, Ontario L6T 2J3 Tel: (905) 456-2033 Fax: (905) 456-1015